





Feptel Enterprise


MSN: feptel@hotmail.com Email: telan@feptel.com



Company website: www.feptel.com Tel:86-755-33106378/28876034







Access controller

Model No.:	MOQ	USD	FEATURE	Picture
F2			1 Metal access fingerprint recognition ;	 95mm*56mm*35mm
			2 Waterproof upto IP65;	
	samples	39.9	3 Local capacity: 200-500 fingerprint templates;	
			4 Standalone fingerprint access controls and fingerprint reader;	
	300	38	5 Attractive outlook and compact module design	
	500pcs	36		
F3			Metal fingerprint access reader	 115mm*70mm*35mm
			Capacity:1000 fingerprints ,2000cards users.	
	samples	55	Can be used as wiegand reader	
	50pcs	52	Can connect extra readers	
	100pcs	49	2 units can be interlocked	
	500pcs	46		
Model No.:	MOQ	USD	FEATURE	Picture
A2	sample	17.9	EM Access control	
	100	16.9	Support 1000users	
	300	15.9	Add or delete card by master cards	
	500	13.9	White/Black color	
K2	Samples	12	Standalone keypads&RFID	
	100	9.9	capacity :500 cards or password;	
	500	9.3	multi-style users,dual-code day/night mode	
			built-in bell control	
			With anti-dismantle alarm	
			Memory, and can keep 500 cards and 510 the user's password	

	sampl	13	Has three ways to open the door.Cards, passwords, card add	
A5	100	12	No card, you can set a password to open the door	
	200	11	With a doorbell button, and Button to open contact	
	500	9		

Model No.:	MOQ	USD	FEATURE	Picture
FC-2011	samples	53	Door control 1	 160mm *106mm 273mm*228mm*65mm
	50pcs	47	Readers can be connected 2 pcs	
	100pcs	45	Control of Memory up to 20,000 Users	
	500pcs	39.9	up to 100,000 Event Buffers	
			Network Communication via RS232 / RS485	
			TCP/IP optional	
			Power supply : USD 19	

Model No.:	MOQ	USD	FEATURE	Picture
FC-2012/4	2-door control			 160mm *106mm 273mm*228mm*65mm
	samples	76	Control 2 or 4 doors	
	50pcs	69	Readers can connected: 4pcs	
	100pcs	67	memory up 20000 uers	
	500pcs	59.9	up to 100,000 Event Buffers	
	4-door control		Network Communication via RS232 / RS485	
	samples	89	English Software supportable database: Access and SQL	
	50pcs	83	TCP/IP optional	
	100pcs	78		
	500pcs	69.9	Big metal power case USD 29	
FC-2011-U	1-door			
	samples	29.9	Support 2 readers	
	100	27.9	Memory up 20000 users	
	200	26	up to 100,000 Event Buffers	





FC-2012/4-U	500	24.5	Network Communication via TCP/IP or RS485	  160mm *106mm 273mm*228mm 273mm*228mm*65mm
	2-door	control		
	samples	39.9	Control 2 or 4 doors	
	100	34	Readers can connected: 4pcs	
	200	33	Memory up to 20000 users	
	500pcs	31.5	up to 100,000 Event Buffers	
	4-door	control	Network Communication via TCP/IP or RS485	
	samples	47	English Software supportable database: Access and SQL	
	100	45		
	200	43	Power supply USD19	
	500pcs	41.5		
FC-12N20&12N20E	samples	183	One to More controllers	 164*106 219 * 115 mm
	50pcs	161		
	100pcs	151	Elevator control system with upto 40 relay outout per controller	
			All system only need one prox reader;	
			Communication by TCP/IP,RS232;	
			With alarm, camera interface;	
			Support patrol, so on functions.	
			Power supply : USD 29	
FC-3011-U	1-door		CCTV- integrated controllers can work with One to More controller	
	samples	38	Support 2 readers	
	100	33	Memory up to 20000 users	
	200	32	up to 100,000 Event Buffers	
FC--3012/4-U	2 door		CCTV- integrated controllers can work with One to More controller	   160mm *106mm 273mm*228mm 273mm*228mm*65mm
	samples	48	Control 2 or 4 doors	
	100	42	Readers can connected: 4pcs	
	200	40	up to 20000 users	
			up to 100,000 Event Buffers	
	4-door		Network Communication via TCP/IP or RS485	
	samples	58	English Software supportable database: Access and SQL	
	100	53.8		
	200	51.8	Power supply USD 16	




Feptel Enterprise



MSN: feptle@hotmail.com Email: telan@feptel.com

Company website: www.feptel.com Tel:86-755-28876034

Access controller

Model No.:	MOQ	USD	FEATURE	Picture
FC-2010 Access Control	Samples	16.5	1 standalone keypads functions keystroke backlight;	
	100	15.9	2 Capacity :1000 users & prox cards;	
	500	14.9	3,With alarm output	
			4,Support anti-dismantle functions	
			6 Non volatile Eeprom memory.	
FC-2010U	Samples	18.8	Standalone keypads&RFID	
	100	17.8	Capacity :500 users .	
	500	16.8	With AUX relay for many extensional uses ;with 2 level security r	
			Support 3 level users for different users.	
			support only keypads	
FC-2010R Card Reader	Samples	42	1 3*4 Matrix keypad;	
	100	39.0	2 Wiegand 26 bit output;	
	200	38.0	3 Proximity cards.	
	300	36.0	4,8 outputs optional ;	
Hot seller FC-AW2-EM	Samples	29.0	Metal waterproof access control upto IP68 ;	
	100	27.9	Support only keypad	
	500	24.6	Capacity 2000 users	
FC-AW2-M	Samples	32.8	can be connected external reader	
	100	31.0		
	500	28.8		120mm*56mm*18mm

FC-AW2-S2-EM	Samples	21.8	Metal waterproof access control upto IP68 ;	 118mm*56mm*20mm	
	100	19.8	Support only keypad		
	500	17.9	Capacity 2000 users		
FC-AW2-S2-M	Samples	27.0	Support EM or mifare		
	100	25.8	can be connected external reader		
	500	23.0			
FC-AW2-S3	Samples	22.0	Metal waterproof access control upto IP68;		 123mm*58mm*18mm
	100PCS	19.0	Support only keypad		
			Capacity 2000 users		
			can be connected external reader		
FC-AW3	For EM	35.0	Metal waterproof access control upto IP68 ;	 120mm*75mm*20mm	
	Samples				
	100	33.0	Support only keypad		
	500	31.0	Capacity 1000 users		
	For mifare		With security mode;		
	Samples	39.0	with secondary code optional;		
100	37.0	With 3 level users ;			
500	35.0				
Model No.:	MOQ	USD	FEATURE	Picture	

			1 wiegand 26 and RS485 output	 46mm*120mm*25mm
			2 Read Range: 5-15cm, Transmit distance: 10C	
			3 waterproof	
R1-EM Card Reader	Samples	9.9	1 Em card reader	
	100	8.0		
	200	7.5		
	500	7.0		
R1-MF Card Reader	Samples	12.0	1 mifare card reader	
	100	9.8		
	200	9.5		
	500	8.8		
	Samples	14.0	EM cards readers	
100	13.0			
			Page:5 Total:12	









R3-EM/MF	200	12.5			 48mm*122mm*27mm
	500	11.8			
	Samples	16.0	Mifare cards readers		
	100	15.0			
	200	14.5			
	500	13.0			
R4	EM		Metal waterproof reader upto IP65;		 120mm*80mm*26mm
	Samples	27.0	EM Mifare optional ;		
	100	25.0	Output wiegand26;		
	300	24.0			
	500	23.0			
	Mifare				
	Samples	29.0			
	100	27.0			
	300	26.5			
500	26.0				
R6-H	Samples	26.0	HID card reader		
	50	25.0	wiegand reader		
	100	23.0			
	500	21.0			
R6-EM					
	Samples	6.0	Mifare cards USB readers		
	100	5.0			
	200	4.8			
	500	4.3			
Model No.:	MOQ	USD	FEATURE	Picture	
FC-2016	Samples	99.0	2000 fingerprints, 50000 records, User name display, Voice prompt, Dry contact	 126mm*189mm*35mm	
	50	95.0	output, USB cable/RS485, TCP/IP		
	100	85.0	Wiegand26, Work code, Time zone access		
			control, Bell schedulers, Short message		

Feptel Enterprise

MSN: feptle@hotmail.com Email:telan@feptel.com

Company website: www.feptel.com Tel:86-755-28876034

Accessories

Model No.:	MOQ	USD	FEATURE	Picture
Mifare cards		0.62	1 Mifare 1K.	
		1.50	2 Mifare 4K.	
HID		2.10	hid cards	
EM cards		0.16	1 Standard shape;	
		0.22	2 Non-standard shape.	
FL-01 Locks	Samples	23.00	1 Electric Bolt.	
	100	20.00		
	500	18.00		
FL-02 Locks	Samples	23.00	1 Electromagnetic Lock.	
	100	20.00		
	500	18.00		
FPS-01 Power supply		11.00		
RS232/RS485 Converter		13.00		
FT-001/4 Exit buttons		4.00	1 Exit buttons .	
panel	Samples	15.0	4-way alarm output	
	100	14.0	Can control: invalid break in alarm, long time unlocking alarm	
			intimidation break in alarm,	
	500	13.0	unlocking linkage ouput, invalid card swiping alarm,	
			integrated fire control alarm	

			Allow to set anti-intimidation password
			Can set long time unlocking alarm time: 0-6000 seconds
			Can set the time delay of each output from 0 to 6000 seconds
Door switch	Samles	5.0	metals shield
			connecting mode: N.C./ N.O.
			rated current : 500(mA), rated voltage : (VDC) 200
			operating distance: more than 35mm, less than90 mm



- Remarks:**
- 1, These offers are based on exchange USD/RMB :6.8,the real offer will change as the exchange when PI.
 - 2, Payment Terms: T/T in advance when total amount is under usd150,000.00 ;
 - 3 50% deposit, balance T/T before shipment when total amount is over usd200,000.00;
 - 4 Price terms: FOB ShenZhen;
 - 5 Packaging: same as our standard or neutral packings;
 - 6 Lead Time: within 2-3weeks upon PI signed and payment received.

1211.9